

## TITLE OF THE INVENTION

Pulsed Volume Control of a Magnetic Ringer

## BACKGROUND OF THE INVENTION

### 1. Field of the Invention

This invention relates in general to audible alerting mechanisms. In particular, the invention discloses a technique for controlling the volume of sound generated by a magnetic transducer, such as those used for producing ringing tones in a telephone system signaling an incoming telephone call.

### 2. Background Art

Telephone receiver products typically include audible ringers to alert users to the presence of an incoming call. Such telephone ringers often employ a form of magnetic transducer to convert an electrical ringing signal into an audible tone. Because telephones are ubiquitous, and used in a wide range of physical environments, most telephones also provide for the user to be able to control the ringer volume produced by the magnetic transducer. As a result, telephones can be used effectively in noisy environments, such as a factory or warehouse, where a high ringer volume is required to ensure that incoming call signals can be heard, as well as in quiet environments, such as an individual office, where a low volume is sufficient to adequately alert the office occupants to an incoming call. Adjustment of ringer volume also allows for the selection of a wide range of personal preferences as to the desired ringer volume.

Many conventional ringers produce their sound by driving a transducer with a square wave signal. One technique for controlling the volume of such a ringer is to vary the amplitude of the square wave signal. This technique is depicted in Figure 1. Figure 1(a) depicts a full volume square wave, while Figure 1(b) depicts a reduced amplitude square wave. However, amplitude control requires that the telephone set include a circuit that produces a driving signal with a variable amplitude. Such circuits typically require an analog driver stage subsequent to the driving signal generator, thereby introducing additional circuit components to the telephone design that would not be necessary if the transducer were driven, for example, solely by a digital controller generating a square wave generated by mere toggling of a digital logic line. These additional analog components increase both the size and the cost of the circuit. Even if a telephone set is designed using components such as an application specific integrated circuit (ASIC), integration of an analog driver section may result in an ASIC with larger die size, more complex design, and reduced reliability than would be the case for a purely digital design. Therefore, it is an object of the invention to provide a ringer with volume control that does not require an analog variable-gain driver.

Another method for controlling the volume of a ringer signal is pulse-width-modulation (PWM), which use results in the signal depicted in Figure 1(c). This technique produces reduced volume by reducing the pulse width of the driving signal. While PWM provides an entirely digital solution to ringer volume control, the disadvantage of this method is that the timbre of the ringer signal (i.e. its harmonic content) changes as the width of driving signal pulses is varied. To the user, this characteristic causes lower volumes to sound "tinnier" than higher volumes, since low

frequency components of the signal are attenuated more than high frequency components when pulse width is reduced. Therefore, it is also an object of this invention to provide a circuit with improved consistency in the tone quality of a ringer sound over a range of ringer volumes that can be implemented as a digital circuit.

These and other objects of the present invention will become apparent in light of the present specifications and drawings.

100504-3331  
T.0323T-4956001

## SUMMARY OF THE INVENTION

A method and apparatus for providing a variable volume audible alert signal is implemented by a digital circuit driving an audio transducer, such as the magnetic transducers commonly utilized as telephone ringers in telephone sets used to signal an incoming telephone call. A full volume ringer driving signal, such as a square wave, in the audible frequency range is first generated. A volume-control signal is also generated, comprising a pulse-width modulated pulse train signal. The full volume ringer signal is multiplied, or amplitude modulated, by the pulse train signal, to generate a resulting output signal that drives a transducer. The frequency of the pulse train signal may be specified as greater than the audible frequency range and/or greater than the transducer cutoff frequency to minimize unwanted audible artifacts. The volume produced by the transducer when driven by the resulting output signal is dependent upon the mark-space ratio of the pulse train signal. However, the timbre of the transducer output in the audio band is relatively consistent, across a range of pulse train signal mark-space ratios.

## BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a time-domain plot of signals typically used to drive audio transducers for prior art telephone ringers.

Figure 2 is a schematic block diagram of a circuit for generating a ringer signal in accordance with the present invention.

Figure 3 is a time-domain plot of ringer signals generated according to the present invention for producing full, medium and low ringer volumes.

Figure 4 is a frequency-domain plot of a ringer output when driven with a full volume signal.

Figure 5 is a frequency-domain plot of a ringer output when driven with a reduced volume ringer signal according to the present invention.

Figure 6 is a plot of ringer output harmonic levels when driven at full, medium and low volumes according to the present invention.

Figure 7 is a frequency-domain plot of a ringer output when driven with a reduced volume ringer signal according to the prior art pulse width modulation technique.

Figure 8 is a plot of ringer output harmonic levels when driven at full and reduced volumes according to the prior art pulse width modulation technique.

## DETAILED DESCRIPTION OF THE DRAWINGS

While this invention is susceptible to embodiment in many different forms, there are shown in the drawings and will be described in detail herein several specific embodiments. The present disclosure is to be considered as an exemplification of the principle of the invention intended merely to explain and illustrate the invention, and is not intended to limit the invention in any way to embodiments illustrated.

According to the present invention, the volume of an audio transducer is controlled by amplitude modulating a ringer tone waveform with a second higher frequency pulse train waveform. The second waveform is pulse width modulated, and the volume of sound produced by the ringer is proportional to the mark-space ratio cycle of the pulse train. While the invention can easily be utilized in conjunction with numerous types of audio transducers known in the art, and for a variety of applications requiring audible notification of a condition or event, it is particularly well suited to the voltage and current requirements of magnetic type ringers commonly used in telephones.

One embodiment of the invention is illustrated in Figure 2. Clock 120 operates as a frequency reference for tone generators 100 and 110. Each tone generator 100 and 110 outputs a digital square wave of predetermined frequency. Cadence control switch 140 operates to periodically toggle switch 160 between the tone generators, such that a standard full volume telephone ringer signal is produced on line 161.

The standard telephone ringer signal is then applied to a first input of switch 170. A second input of switch 170 is connected to ground. The state of switch 170 is controlled by volume pulse control circuit 150, which generates a pulse width modulated ("PWM") control signal 151. Circuit 150 receives two clock reference signals. Clock 120 provides a

signal defining the frequency at which switch 170 is toggled. Clock 130 provides a clock signal of frequency higher than that of clock 120, which controls the resolution of the mark-space ratio of PWM control signal 151. Signal 151 causes switch 170 to rapidly switch between the ringer tone on line 161 when signal 151 resides in the logic high, or mark, state, and a silent, grounded input when signal 151 resides in the logic low, or space, state. The resulting output 180 of switch 170 is a volume controlled ringer signal, which is applied to a transducer.

In the embodiment of Figure 2, the number of discrete volume levels that can be produced is determined by the ratio of clock 130 to clock 120. The actual volume selection is controlled by a signal on line 155. In the illustrated embodiment, with a 1024kHz frequency of clock 130, and a 64 kHz clock 120, the number of volume settings is 16. Specifically, for each positive going half of a cycle of clock 120, clock 130 cycles 16 times. Therefore, the signal from clock 120 can be pulse width modulated with mark-space ratios between 6.25%, where the PWM signal mark is one cycle of clock 130 and the space lasts 15 cycles of clock 130, and 100%, in which the PWM signal mark lasts through all sixteen cycles of clock 130.

The ringer circuit of Figure 2 is a block diagram illustrating the basic building blocks of the present invention, the function of which can readily be implemented using a variety of alternative digital logic configurations know to those skilled in the art. For example, the function of switch 170 could readily be implemented with identical result by using a digital multiplier, or a digital logic AND gate, either one of which would receive lines 161 and 151 as inputs.

The waveforms generated by the ringer driving circuit are shown in Figure 3. Figure 3(a) depicts a full volume ringer signal according to the present invention. At full volume, the duty cycle of control signal 151 is 100%. Therefore, switch 170 is maintained in its illustrated position, such that the square wave ringer tone on line 161 is passed to output 180 unaltered. A frequency spectrum analyzer measurement of a magnetic transducer driven by the pure, full volume square wave ringer output of Figure 3(a) appears in Figure 4. The plot illustrates the concentration of energy in the odd numbered harmonics of the fundamental ringer frequency, which is characteristic for a square wave signal. Thus, at full volume, the present invention produces a tone of conventional timbre, with which many users may be familiar.

Figure 3(b) illustrates a medium volume ringer signal waveform according to the present invention. Volume pulse control circuit 150 receives a signal requesting medium ringer volume on line 155. Control circuit 150 generates a 64 kHz PWM pulse train with a 50% mark-space ratio, such that control signal 151 alternates between a mark during eight consecutive cycles of clock 130, followed by a space during the subsequent eight cycles of clock 130. Signal 151 causes output 180 of switch 170 to rapidly and evenly alternate between the ringer tone of line 161, and ground, resulting the ringer signal depicted in Figure 3(b).

Figure 5 is a frequency spectrum analyzer plot of the output of a magnetic transducer driven by the medium volume waveform of Figure 3(b). As with the full volume output of Figure 4, the reduced volume output of Figure 5 shows audible energy concentration at the odd harmonics, as is characteristic of a pure square wave signal. However, the amplitudes of each harmonic are substantially reduced in comparison to the



pure square wave output of Figure 4. Thus, a reduced volume ringer tone is produced with a "square wave timbre". The variable volume ringer signal is thus generated entirely digitally without requiring any analog, variable gain amplifier circuits.

Figure 3(c) demonstrates a further reduced volume ringer signal, in which switch 170 is controlled by volume control circuit 150 generating a 64 kHz PWM pulse train with a mark-space ratio of 6.25%. Specifically, signal 151 remains in a mark state for one cycle of clock 130, followed by fifteen cycles of the space state. Thus, output 180 is comprised of one cycle of signal 161, alternating with fifteen cycles of grounded signal.

As with the waveform of Figure 3(b), a ringer driven by the Figure 3(c) waveform generates an audio signal with odd harmonics, such that its tonal quality is much like that of a square wave. However, the volume of the output is even further reduced, thus enabling an even lower ringer volume setting, again implemented without requiring any variable gain analog amplifier. Additional intermediate volume settings can be achieved by implementing intermediate pulse train mark-space ratios.

Figure 6 compares the power levels of the odd signal harmonics for each of the transducer driving waveforms of Figure 3. Specifically, the pure square wave of Figure 3(a) corresponds to the power levels plotted in Figure 6(a). Likewise, the waveform of Figure 3(b) corresponds to the power levels of Figure 6(b), and the waveform of Figure 3(c) corresponds to the power levels of Figure 6(c). Figure 6 illustrates that the power ratios between harmonics for the reduced volume levels of Figures 6(b) and 6(c), remain similar to the ratios for the pure square wave signal of Figure 6(a). Thus, the tonal quality of the transducer output is preserved despite the reduction in output power.

By contrast, Figure 7 depicts the frequency spectrum output of a magnetic transducer driver by a reduced-volume PCM signal, such as that of Figure 1(c). The spectrum reveals the presence of substantial levels of even harmonics. Moreover, the odd harmonic level proportions of Figure 7 differ substantially from those of Figures 4 and 5, falling off more slowly. Figure 8 illustrates the substantial differences between the harmonic power levels of the transducer driven by a pure square wave (Figure 8(a)), and the transducer driven by the prior art reduced-volume PCM signal (Figure 8(b)). Thus, the prior art PCM signal of Figure 1(c) causes the ringer tone to change as volume is reduced, becoming tinny, whereas the present invention provides for a digitally implemented, variable volume ringer with consistent tonal quality.

While the illustrated embodiment employs frequencies of 64 kHz and 1024 kHz for clocks 120 and 130, respectively, other frequencies can readily be implemented. However, in selecting operational frequencies, attention should be paid to the avoidance of undesired signal distortion due to mixing products, and the tradeoff between power consumption and volume setting resolution.

In operation, the invention involves the multiplication, or amplitude modulation, of the full-volume ringer signal by the PWM pulse train, to generate a reduced amplitude baseband signal. However, modulation inherently generates additional mixing products that can potentially lead to audible distortion of the ringer output. To reduce the risk of audible distortion caused by mixing products, the frequency of the PWM pulse train can be selected to be above the audible frequency range, and/or the passband of the transducer.

Furthermore, even to the extent that the pulse train frequency lies beyond the audible frequency range, many transducers exhibit nonlinearities in their response that can

cause high frequency mixing products to be folded back into the audible bandwidth. Therefore, audible artifacts may be reduced when using a transducer with substantial nonlinearities by choosing a pulse train frequency well above the transducer cutoff.

Finally, a tradeoff between power consumption and volume setting resolution may be considered in choosing the frequency of clock 130. The greater the ratio between the frequencies of clocks 130 and 120, the greater the range and resolution of volume settings that can be produced. However, the power consumption of the digital circuitry also increases with increased clock speeds. Appropriate clock speeds can be chosen based upon design considerations for a particular application.

The foregoing description and drawings merely explain and illustrate the invention and the invention is not limited thereto except insofar as the appended claims are so limited, inasmuch as those skilled in the art, having the present disclosure before them will be able to make modifications and variations therein without departing from the scope of the invention.